



ALUMINIUM PLATFORM STEP LADDERS STANDARD RANGE

150KG RATED | AS 1892 LENGTHS .61 m - 2.3 m

LIGHTWEIGHT

Strongest double hollow step treads

STRENGTH

World's safest aluminium platform ladders 500kg load tested Swagelock step connection 50% stronger

SOLID FOUNDATION

Channel section rear frame
Strongest foot connection andstronger full gusset base brace system - "GUSSET GUTZ"







CODE	PLATFORM HEIGHT (m)	WIDTH (mm)	WEIGHT (kg)	TRANSPORT CUBE (m³)
PS5-2G	.61	580	9	.33
PS6-3G	.88	620	10	.39
PS7-4G	1.17	660	11	.45
PS8-5G	1.45	700	12	.51
PS9-6G	1.74	740	13	.57













All measurements are nominal and do not indicate 'exact weights and measures'





ALUMINIUM PLATFORM STEP LADDERS PREMIUM RANGE

150KG RATED | AS 1892 LENGTHS .61 m - 3.45 m

LIGHTWEIGHT

Strongest double hollow step treads

STRENGTH

World's safest aluminium platform ladders 500kg load tested Swagelock step connection 50% stronger

SOLID FOUNDATION

Stronger RHS section rear frame Strongest foot connection and strongbow base brace system

















C	ODE	PLATFORM HEIGHT (m)	WIDTH (mm)	WEIGHT (kg)	TRANSPORT CUBE (m³)
Р	S5-2	.61	580	9	.33
Р	S6-3	.88	620	10	.39
P	S7-4	1.17	660	11	.45
Р	S8-5	1.45	700	12	.51
P	S9-6	1.74	740	13	.57
P:	S10-7	2.02	780	14	.63
Р	S11-8	2.30	820	15	.69
PS	313-10	2.89	860	24	1.22
PS	615-12	3.45	1050	26	1.4

All measurements are nominal and do not indicate 'exact weights and measures'

