







FIBREGLASS PLATFORM STEP LADDERS STANDARD RANGE

150KG RATED | AS 1892 LENGTHS .61 m - 1.74 m

LIGHTWEIGHT

Strongest double hollow step treads

STRENGTH

World's safest fibreglass platform ladders 500kg load tested

Swagelock step connection 50% stronger

UV RESISTANT FIBREGLASS - lasts longer and better value

SOLID FOUNDATION

Channel section rear frame
Strongest foot connection and stronger full gusset base brace system - "GUSSET GUTZ"







CODE	PLATFORM HEIGHT (m)	WIDTH (mm)	WEIGHT (kg)	TRANSPORT CUBE (m³)
FPS5-2G	.61	580	11	.21
FPS6-3G	.88	620	12	.26
FPS7-4G	1.17	660	13	.32
FPS8-5G	1.45	700	14	.39
FPS9-6G	1.74	740	15	.46















All measurements are nominal and do not indicate 'exact weights and measure











FIBREGLASS PLATFORM ADDERS PREMIUM RANGE

150KG RATED | AS 1892 LENGTHS .61 m - 2.89 m

LIGHTWEIGHT

Strongest double hollow step treads

STRENGTH

World's safest fibreglass platform ladders 500kg load tested Swagelock step connection 50% stronger UV RESISTANT FIBREGLASS - lasts longer and better value

SOLID FOUNDATION

Stronger RHS section rear frame Strongest foot connection and strongbow base brace system





CODE	PLATFORM HEIGHT (m)	WIDTH (mm)	WEIGHT (kg)	TRANSPORT CUBE (m³)
FPS5-2	.61	580	11	.33
FPS6-3	.88	620	12	.39
FPS7-4	1.17	660	13	.45
FPS8-5	1.45	700	14	.51
FPS9-6	1.74	740	15	.57
FPS10-7	2.02	780	16	.63
FPS11-8	2.30	820	17	.69
FPS13-10	2.89	1050	26	1.22













All measurements are nominal and do not indicate 'exact weights and measures'



