## **Options and Specifications**

Available in three ranges: Standard, Deluxe and Premium Available in eight different lengths, from 1.5m to 6m For a small fee, plank ends can be stamped with the owner's name and phone number. 205kg working load limit Maximum single plank spar8m Altech Supasafe Planks conform to Australian standards AS 1577-1993

## altech supasafe planks

Altech Supasafe Planks are not only the best All our planks feature four unique vee-grooved value for money planks in the Australian market, knurls on each side for superior grip. In addition to but they also represent uncompromised quality and this, our Deluxe and Premium ranges are equipped innovation in many aspects of safety and performance. with superior EPDM rubber friction strips that are ribbed for firmer foothold. The use of structural-grade aluminum alloy in the manufacture of all Altech Supasafe Planks, delivers extra strength and durability, providing peace of mind and many years of trouble free use.

Unlike other manufacturers, our Supasafe Planks come in three ranges – Standard, Deluxe and Premium thus catering for a range of price points and applications.

## Featu

Knurled Ri Knurled Ri Rubber Str **Rubber Str** 



Standard





internal stiffening webs to provide increased rigidity and greater impact resistance.

Premium

Altech's commitment to quality means our planks have tough cast aluminium end caps fitted with countersunk head rivets, avoiding protruding heads and unsightly welded joints. They also feature two strong internal stiffening webs to provide increased rigidity and greater impact resistance.

Using our compact and lightweight Altech Twin-Plank Clamps, two planks can be quickly and easily joined to form a 450mm wide twin-plank working platform.

re Comparison		
Standard	Deluxe	Premium
$\checkmark$	$\checkmark$	$\checkmark$
$\checkmark$	$\checkmark$	$\checkmark$
-	-	$\checkmark$
-	✓	$\checkmark$
	•	•

Altech Supasafe Planks feature two strong Knurled Ribs for superior grip on top and base Anti-slip ribbed Rubber Strips

## altech supasafe clamps

Our lightweight Altech Twin-Plank Clamps allow you to join together two Altech Supasafe Planks to form a twin-plank working platform that then enables a wider span. Manufactured exclusively for use with Altech Supasafe Planks, and a choice of Standard, Deluxe or Premium planks, Altech Twin-Plank Clamps are compact and easy to use.

There are no bulky clamps over the plank surface to cause a tripping hazard.

Two Altech Twin-Plank Clamps along with two S upasafe Planks form a 450mm wide work platform with a 205kg Working Load Limit, enabling a maximums pan of 5 metres. This conforms to Australian S tandard AS 6001-1999.

W.L. LIMIT: 200 KG MAX SPAM: 2.75 M COMPLIES: AS 1577

MANUFACTURED BY ALTECH EQUIPMENT VIC: 3429 AUSTRALIA

Altech Twin-Plank Clamps are simple to install

- 1. Place two Altech Supasafe Planks side-by-side on trestle rungs at the required height.
- 2. Slide two AI tech Twin-Plank Clamps into position between the planks and space evenly across the span with bolt-heads upright.
- 3. Tighten clamps with allen key provided, ensuring top and bottom curved clamp jaws are engaged with the planks' corner ribs.
- 4. The twin-plank working platform is ready to use.



Altech Supasafe Clamps should be positioned approximately 1/3 of the plank length in from the plank ends, and can easily be fitted with an allen key

